VANTREM

GEOMETRIC / 90° ROTATIONS



Nine broad planes draw a grid of soft shadows.

Setting

GEOMETRY AND FORMAT

The piece



01 Front view



02 Three-quarter view

GYP-STD-012-A-01

Material	Fibre-reinforced plaster
Type	3D wall panel
Finish	Matt white · Fine mineral texture
Reference	GYP-STD-012-A-01
Format	500 × 500 mm
Total thickness	10–21 mm
Maximum relief	11 mm
Reference weight	5.09–5.51 kg
Coverage per panel	0.25 m^2
Use	Interior cladding in dry areas
Finish as supplied	Matt white, ready to prime and paint
Panels per m^2	4 panels/m^2
Repeat	One module · 90° rotations

DESIGN AND CONTINUITY

Relief in the space



Cladding detail

The motif

Three rows of large squares combine gentle inclines on a continuous plaster base. Side light reveals the transitions of the relief; rotating the piece extends the rhythm across the whole wall.

01 Laying

Align the grid and follow the reference composition in the diagram: 270° and 180° at the top, 0° and 90° at the bottom. Fill the joints between pieces with plaster, keeping the channels and inclines that are part of the design.

02 Joints

Joints between pieces filled with plaster. Keep the fine channels of the grid and the original inclines.

03 Reaction to fire

In preparation: formulation intended for class A1. Collection technical data sheet and installation guide available to download from the design's web page.