FLUVA

WAVES AND FOLDS / SAME ORIENTATION



Horizontal bands of varying width run across the plaster like a continuous riverbed.

Setting

GEOMETRY AND FORMAT

The piece



01 Front view



02 Three-quarter view

GYP-STD-013-A-01

Material	Fibre-reinforced plaster
Type	3D wall panel
Finish	Matt white · Fine mineral texture
Reference	GYP-STD-013-A-01
Format	500 × 500 mm
Total thickness	10–29 mm
Maximum relief	19 mm
Reference weight	5–5.41 kg
Coverage per panel	0.25 m^2
Use	Interior cladding in dry areas
Finish as supplied	Matt white, ready to prime and paint
Panels per m^2	4 panels/m^2
Repeat	One module · Same orientation

DESIGN AND CONTINUITY

Relief in the space



Cladding detail

The motif

Broad curves link with fine undulations and delicate crossings. Horizontal and vertical repetition extends the relief without interruption, while side light picks out the changes in width and depth.

01 Laying

Lay the pieces with the bands horizontal and keep the same orientation, without rotating them. Align the profiles and fill the joints with plaster, keeping the undulations and crossings of the design.

02 Joints

Joints filled with plaster to form a continuous surface; keep the bands and undulations of the design.

03 Reaction to fire

In preparation: formulation intended for class A1. Collection technical data sheet and installation guide available to download from the design's web page.