VELIN

LINEAR / FIXED ORIENTATION



Four vertical folds and flat facets make up a continuous relief that changes with side light.

Setting

GEOMETRY AND FORMAT

The piece



01 Front view



02 Three-quarter view

GYP-STD-048-A-01

Material	Fibre-reinforced plaster
Type	3D wall panel
Finish	Matt white · Fine mineral texture
Reference	GYP-STD-048-A-01
Format	500 × 500 mm
Total thickness	10–25 mm
Maximum relief	15 mm
Reference weight	5.21–5.64 kg
Coverage per panel	0.25 m^2
Use	Interior cladding in dry areas
Finish as supplied	Matt white, ready to prime and paint
Panels per m^2	4 panels/m^2
Repeat	One module · Fixed orientation

DESIGN AND CONTINUITY

Relief in the space



Cladding detail

The motif

Steps at different heights vary the vertical rhythm. Repeating a single piece lets the design extend across the whole wall, with the joints filled and blended into the surface.

01 Laying

Repeat the module in the same orientation, without rotating the pieces or offsetting the rows. Fill the joints with plaster and finish them flush to keep the relief continuous.

02 Joints

White fibre-reinforced plaster base. Joints are filled with plaster and finished flush so the relief blends into the wall.

03 Reaction to fire

In preparation: formulation intended for class A1. Collection technical data sheet and installation guide available to download from the design's web page.