PLEVA

LED PANELS / ROTATIONS AND ALIGNMENT AS PER DESIGN



Vertical folds that fade towards the bottom and a continuous cornice of light.

Setting

GEOMETRY AND FORMAT

The piece



01 Front view



02 Three-quarter view

GYP-LED-065-A-01

Material	Fibre-reinforced plaster
Type	3D wall panel
Finish	Matt white · Fine mineral texture
Reference	GYP-LED-065-A-01
Format	500 × 500 mm
Total thickness	9.5–30 mm
Maximum relief	20.5 mm
Reference weight	4.28 kg
Coverage per panel	0.25 m^2
Use	Interior cladding in dry areas
Finish as supplied	Matt white, ready to prime and paint
Panels per m^2	4 panels/m^2
Repeat	One module · Rotations and alignment as per design

DESIGN AND CONTINUITY

Relief in the space



Cladding detail

The motif

PLEVA combines a smooth upper band with eight vertical folds at a 62.5 mm pitch. An inclined plane gradually cuts back the relief until it disappears at the lower edge. The cornice hides the light and lets the channel run continuously across the width of the wall. Plaster panel designed for indirect LED light. Designed to house a 24 V silicone LED profile. The set is planned with a profile and power supply, with components to be confirmed. Calculated reference weight: 4.28 kg.

01 Laying

Keep rows and columns aligned in the same orientation. A 180° rotation reverses the direction of the light. Keep the cornices and folds when filling the joints; do not fill the housings. The channel and strip are fitted after laying and painting. Furniture and light fittings need support independent of the panel.

02 Joints

Joints between panels filled; keep the relief and the lighting housings.

03 Reaction to fire

In preparation: formulation intended for class A1. Collection technical data sheet and installation guide available to download from the design's web page.