HOLVREA

LED PANELS / ROTATIONS AND ALIGNMENT AS PER DESIGN



A central disc and concentric waves form a halo of light.

Setting

GEOMETRY AND FORMAT

The piece



01 Front view



02 Three-quarter view

GYP-LED-067-A-01

Material	Fibre-reinforced plaster
Type	3D wall panel
Finish	Matt white · Fine mineral texture
Reference	GYP-LED-067-A-01
Format	500 × 500 mm
Total thickness	9.5–30 mm
Maximum relief	20.5 mm
Reference weight	3.93 kg
Coverage per panel	0.25 m^2
Use	Interior cladding in dry areas
Finish as supplied	Matt white, ready to prime and paint
Panels per m^2	4 panels/m^2
Repeat	One module · Rotations and alignment as per design

DESIGN AND CONTINUITY

Relief in the space



Cladding detail

The motif

HOLVREA combines a smooth 250 mm diameter disc with six concentric waves of decreasing relief. The channel beneath the edge of the disc creates indirect lighting on the plaster. Plaster panel designed for indirect LED light. Designed to house a 24 V silicone LED profile. The set is planned with a profile and power supply, with components to be confirmed. Calculated reference weight: 3.93 kg.

01 Laying

Align the 500 mm modules. The symmetry of the piece lets you rotate it without changing its pattern. Fill the joints between pieces while keeping the circles, waves and housings. Plan the curved channel, connections, power supply and access with the project professional. Furniture and light fittings need support independent of the panel.

02 Joints

Joints between panels filled; keep the relief and the lighting housings.

03 Reaction to fire

In preparation: formulation intended for class A1. Collection technical data sheet and installation guide available to download from the design's web page.